



## PRIMAL™ AC-8188 Acrylic Emulsion

New high performance polymer for stone paints and texture coatings

### Regional Product Availability

- Asia-Pacific

### Description

PRIMAL™ AC-8188 Acrylic Emulsion is an acrylic polymer designed for high performance stone paints and texture coatings. Coatings manufactured with PRIMAL™ AC-8188 Acrylic Emulsion have excellent UV resistance and outdoor durability and offers excellent water resistance, alkali resistance, heat-age stability and early cracking resistance properties. PRIMAL™ AC-8188 Acrylic Emulsion is manufactured with a proprietary cross-linking technology that offers excellent adhesion on various substrates, such as brick, cement and glass.

### Key Features

- 100% acrylic polymer composition.
- APEO free\*.
- Excellent mechanical stability and calcium ion (Ca<sup>2+</sup>) stability.
- Manufactured with a proprietary cross-linking technology.
- Good film formation.

### Benefits

- Excellent water whitening resistance.
- Excellent weather durability.
- Excellent adhesion on various substrates
- Good crack resistance.

### Typical Properties

(These properties are typical but do not constitute specifications).

| Property                                   | Typical Values        |
|--|-----------------------|
| Appearance                                 | Milky white emulsion  |
| Solids, by weight, %                       | 46.5                  |
| Density (g/ml), wet                        | 1.04                  |
| pH   | 8                     |
| Minimum Film Formation Temperature (± 2°C) | 25                    |
| Viscosity (Brookfield LVT #3, 60 rpm), cps | < 1500                |
| Storage precautions                        | Protect from freezing |

\*Manufactured without the use of APEO surfactants..

**Handling  
Precautions**

Before using this product, consult the Material Safety Data Sheet (MSDS)/Safety Data Sheet (SDS) for details on product hazards, recommended handling precautions and product storage.

**Storage**

Store products in tightly closed original containers at temperatures recommended on the product label.

**Disposal**

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Coating Materials Technical Representative for more information.

**Chemical  
Registration**

Many countries within the Asia-Pacific require the registration of chemicals, either imported or produced locally, prior to their commercial use. Violation of these regulations may lead to substantial penalties imposed upon the user, the importer or manufacturer, and/or cessation of supply. It is in your interests to ensure that all chemicals used by you are registered. Dow does not supply unregistered products unless permitted under limited sampling procedures as a precursor to registration.

**Note on  
Asia-Pacific  
Product Line**

Product availability and grades vary throughout the countries in Asia-Pacific. Please contact your local Dow Coating Materials representative for further information and samples.

**Product  
Stewardship**

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

**Customer Notice**

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

**Contact:**

Australia / NZ +61-3-9272-4222  
South East Asia +65-6861-1077  
Greater China +86-21-3851-1000  
Japan +81-3-6238-4300  
Korea +82-11-265-3736  
India +91-22-6602-8888  
<http://www.dowconstructionchemicals.com>

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

UNRESTRICTED – May be shared with anyone

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow Form No. xxx-xxxxx-xxxx-xxx-EN  
PRIMAL™ AC-8188 Acrylic Emulsion / Dow Construction Chemicals

05/2013, Rev.0